

REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1 to 6 in the underlying PCT Application No. PCT/EP2003/10458 and adds new claims 7 to 13. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and does not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/EP2003/10458 includes an International Search Report, dated March 3, 2004, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

The underlying PCT Application No. PCT/EP2003/10458 also includes an International Preliminary Examination Report, dated February 14, 2005. A copy of the International Preliminary Examination Report and annex thereto are included herewith.

It is respectfully submitted that the subject matter of the present application is new, non-obvious and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

KENYON & KENYON

Dated: May 9, 2005

By: 

Richard L. Mayer
Reg. No. 22,490
One Broadway
New York, New York 10004
(212) 425-7200
CUSTOMER NO. 26646

BN 42,114

MOTOR VEHICLE STEERING COLUMN

FIELD OF THE INVENTION

The **present** invention relates to a motor vehicle steering column with a bracket fixed to the vehicle and a steering column tube ~~in accordance with the precharacterizing clause of patent claim 1.~~

BACKGROUND INFORMATION

~~DE~~ **German Published Patent Application No. 196 41 152 A1** ~~discloses~~ **describes** a motor vehicle steering column, in which a steering column tube can be adjusted in inclination relative to a bracket fixed to the vehicle via an adjusting device. The adjusting device ~~comprises~~ **includes** a lever which is mounted pivotably on the bracket and can be deflected about a pivot axis by ~~means of~~ a driving device -- here an electric motor. The driving device drives a drive spindle on which a spindle nut is seated. The forward movement of the spindle nut causes the lever to be deflected on the bracket about a pivot axis, so that the steering column tube which is connected to the lever is carried along upward or downward.

This ~~solution~~ **arrangement** has the drawback that, for relatively large adjustments, the lever length has to be correspondingly enlarged. However, it is precisely in the cockpit region that the construction space available is not as desired.

SUMMARY

~~It is therefore the object~~ **According to an example embodiment** of the **present** invention ~~to provide,~~ a motor vehicle steering column **is provided** which ~~permits~~ **may permit** a maximum inclination setting irrespective of the available construction space.

~~This object is achieved according to the invention by the features of patent claim 1.~~

According to the an example embodiment of the present invention,
an adjusting device for the inclination setting of a steering
column tube is provided, which device ~~comprises~~ includes a lever
which is mounted pivotably on a bracket fixed to the vehicle and
5 to the output end of which is coupled a deflecting clamp. The
deflecting clamp is connected pivotably to the steering column tube,
so that, when the lever is deflected, the deflecting clamp and
therefore the steering column tube are carried along. The
transmission ~~ration~~ ratio between the lever and deflecting clamp
10 is ~~designed in~~ arranged such-a-manner that a small deflection of
the lever ~~causes~~ may cause a large adjustment of the deflecting
clamp. Depending on the arrangement of the pivot axis of the lever
and of the deflecting clamp, the adjustment of the steering column
~~can~~ may be selected freely without having an increased need for
15 construction space.

~~Advantageous refinements emerge from the subclaims.~~

In ~~one preferred~~ an example embodiment, the steering column tube
20 ~~can~~ may be mounted on the bracket ~~in-a-manner~~ such that it ~~can~~ may
be moved on a pivot axis extending transversely with respect to
the longitudinal axis of the motor vehicle steering column. This
pivot axis forms the pivot point of the motor vehicle steering
column during the inclination setting. That is ~~to say~~, the further
25 away the pivot axis is arranged from the steering wheel, the greater
the adjustments which ~~can~~ may be achieved for the steering wheel
by ~~means of~~ small adjustments of the adjusting device.

In addition to an inclination setting, the steering column tube
30 may also be held ~~in-a-manner~~ such that it ~~can~~ may be set in length.
For this purpose, two steering column sections which ~~can~~ may be
displaced one inside the other are provided, with, below the
longitudinal axis of the motor vehicle steering column, a flange
being integrally formed on the outer steering column tube section.
35 The integrally formed flange has a pivot axis of the deflecting

clamp passing through it. The adjustment during the inclination setting ~~can~~ may be determined as a function of the position of the pivot axis. The closer the pivot axis of the deflecting clamp is to the pivot axis of the lever, which axis is fixed on the vehicle,
5 the greater the adjustments which are possible.

The deflecting clamp ~~can~~ may have an ~~essentially~~ a substantially U-shaped ~~design~~ configuration guided around the outer steering column tube section below. The free limb ends of the deflecting
10 clamp ~~can~~ may be coupled to the output end of the lever. This ~~improves~~ may improve the stiffness of the entire system.

The lever ~~can~~ may have an ~~essentially~~ a substantially triangular longitudinal section form, so that the driving end is formed by
15 a point of the triangle and the output end by another point of the triangle. The limb lengths of the triangular lever determine the lever ratios of the adjusting device.

The lever may be ~~designed~~ arranged mirror-symmetrically with
20 respect to the longitudinal axis of the motor vehicle steering column, so that precise height setting without a lateral offset is possible.

~~Two exemplary~~ Exemplary embodiments hereof are explained below
25 with reference to the ~~drawing, in which:~~ appended Figures.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows is a perspective view of an example embodiment of a
motor vehicle steering column ~~in a first embodiment in a~~
30 ~~perspective view,~~

Fig. 2 shows is a side view of the motor vehicle steering column
~~as shown~~ illustrated in Fig. 1 ~~in a view from the side, and.~~

Fig. 3 ~~shows~~ is a side view of an example embodiment of a motor vehicle steering column ~~in a second embodiment.~~

DETAILED DESCRIPTION

- 5 Fig. 1 illustrates a motor vehicle steering column 1 with a two-part, telescopic steering column tube 2, in which a steering spindle 3 is rotatably mounted. The steering column tube 2 is connected to a bracket ~~(not illustrated)~~ which is fixed to the vehicle.
- 10 The steering column tube 2 ~~is composed of~~ includes an inner steering column tube section 4 and an outer steering column tube section 5. The inner steering column tube section 4 is connected to a threaded spindle 6 which is driven by an electric motor 7. Depending on the direction of rotation of the threaded spindle 6,
- 15 the inner steering column tube section 4 is moved into or out of the outer steering column tube section 5 in accordance with the arrow direction A, so that the motor vehicle steering column 1 is set comfortably in the longitudinal direction.
- 20 A second electric motor 8 is fastened to a mount 9 on the outer steering column tube section 5. The outside of the mount 9 has two axle stubs 10 which together form a pivot axis 11. The axle stubs 10 are mounted pivotably in receptacles of the bracket.
- 25 A second threaded spindle 12 is driven by the electric motor 8, so that -- depending on the direction of rotation of the threaded spindle 12 -- a spindle nut 13 sitting on the threaded spindle 12 is moved to and fro in accordance with the arrow direction B.
- 30 The spindle nut 13 belongs to an adjusting device 14 via which the steering column tube 2 is held ~~in such a manner~~ that it ~~can~~ may be adjusted in inclination relative to the bracket fixed to the vehicle.

The adjusting device 14 ~~comprises~~ includes a lever 15 and a deflecting clamp 16. The lever 15 has a driving end 17 and an output end 18.

5 The driving end 17 is fastened pivotably to the spindle nut 13, so that the lever 15 ~~can~~ may execute a pivoting movement in accordance with arrow direction C about a pivot axis 19. From the driving end 17, the lever 15 extends in an angular manner to the output end 18 to which the deflecting clamp 16 is coupled via a
10 pivot axis 20, so that the deflecting clamp 16 ~~can~~ may be moved about the pivot axis 20 in accordance with arrow direction D.

The lever 15 is provided with bearing journals 21 which are mounted in corresponding receptacles of the bracket and therefore form a
15 pivot axis 22 about which the lever 15 ~~can~~ may be pivoted in accordance with arrow direction E.

At its end 23 ~~lying~~ located opposite the pivot axis 20, the deflecting clamp 16 coupled to the output end 18 of the lever 15
20 is mounted pivotably on a flange 24 of the outer steering column tube section 5, so that a movement of the deflecting clamp 16 about a pivot axis 25 in accordance with arrow direction F is possible.

Fig. 2 illustrates the motor vehicle steering column 1 (which is
25 illustrated perspectively in Fig. 1) in a view from the side. In addition to the motor vehicle steering column 1, a bracket 26 which is fixed to the vehicle is indicated.

The motor vehicle steering column 1 is mounted on the bracket 26
30 via a clip 28 (illustrated schematically) ~~in such a manner~~ that the motor vehicle column 1 ~~can~~ may move in a circular path in accordance with arrow direction G about a pivot axis 27 extending transversely with respect to the longitudinal axis L of the motor vehicle steering column 1. The movement of the motor vehicle
35 steering column 1 along the arrow direction G is realized by ~~means~~

of the adjusting device 14 and offers the occupant the possibility of undertaking an inclination setting of the steering wheel.

The inclination adjustment by ~~means of~~ the adjusting device 14
5 takes place as follows:

starting from that position of the motor vehicle steering column 1 which is indicated in Fig. 2 by a solid line, the electric motor 8 is activated by the driver, so that the threaded spindle 12
10 rotates. As a result, the spindle nut 13 sitting on the threaded spindle 12 is moved in the arrow direction B into the position illustrated by chain-dotted lines and the lever 15 is therefore deflected about its pivot axis 22 in accordance with arrow direction E. During its movement, the output end 18 of the lever
15 15 carries along the deflecting clamp 16, with the result that the latter rotates about the pivot axis 25 in accordance with arrow direction F and, in the process, moves the motor vehicle steering column 1 upward in arrow direction G. This movement takes place on a circular path about the pivot axis 27 of the motor vehicle
20 steering column 1.

During an opposed movement of the spindle nut 13, the movements of the adjusting device 14 ~~run~~ are correspondingly ~~in reverse~~ reversed.

25 That movement of the spindle nut 13 which ~~runs~~ is on a circular path about the pivot axis 22 is compensated for by the pivotable mounting of the electric motor 8 or mount 9 permitting a pivoting movement of the threaded spindle 12 about the pivot axis 11.
30 However, this compensation may also be achieved by a slotted-guide mechanism or a flexible threaded spindle.

Fig. 3 ~~shows a second~~ illustrates an example embodiment of the ~~invention~~ hereof, with the same reference numbers as in Figs. 1 and 2 being used. Components which differ from the example
35

embodiment ~~according to~~ illustrated in Figs. 1 and 2 are indicated
by an apostrophe accompanying prime.

In the case of the second example embodiment of the invention as
5 shown illustrated in Fig. 3, the adjusting device 14' ~~comprises~~
includes a lever 15', the pivot axis 22' of which, in contrast to
the example embodiment ~~according to~~ illustrated in Figs. 1 and 2,
is shifted forward in the direction of the steering wheel. This
has the advantage inter alia may provide that, in the event of a
10 crash, the forces introduced into the steering column cause a
tensile stress in the threaded spindle 12.

The inclination setting by ~~means of~~ the adjusting device 14' takes
place as follows:

15 The threaded spindle 12 is driven by the electric motor 8, so that
the spindle nut 13 moves on the threaded spindle 12 in accordance
with arrow direction B. The lever 15' is deflected about the pivot
axis 22' in accordance with arrow E', as a result of which the pivot
20 axis 20' is correspondingly shifted downward. The deflecting clamp
16 is pivoted about the pivot axis 25' in accordance with arrow
direction F', so that the motor vehicle steering column 1 moves
downward on a circular path about the pivot axis 27 in accordance
with arrow direction G'.

25 In the case of a movement of the spindle nut 13 in the opposite
direction, the sequence of movement of the adjusting device 14'
takes place in the reverse direction.

30 In this example embodiment ~~too~~, the movement of the spindle nut
13 can may be compensated for by the pivotable mounting of the
electric motor 8 or the mount 9.

Abstract

ABSTRACT

The invention relates to a A motor vehicle steering column (1) with
includes a bracket fixed to the vehicle and a steering column tube
5 (2). The steering column tube ~~can~~ may be adjusted in inclination
relative to the bracket fixed to the vehicle via an adjusting device
(14). The adjusting device (14) ~~comprises~~ includes a lever (15)
which is mounted pivotably on the bracket and ~~can~~ may be deflected
about a pivot axis (22) by ~~means of~~ a driving device (8). It is
10 ~~the object of the invention to provide a~~ The motor vehicle steering
column which ~~permits~~ may permit a maximum inclination setting
irrespective of the available construction space. ~~This object is~~
~~achieved in that a~~ A deflecting clamp (16) which is connected
pivotably to the steering column tube (2) is coupled to an output
15 end (18) of the lever (15).

~~(Fig. 1)~~